

BYD's Dream All Human Hope

Changing human dependence on non-renewable energy as the starting point, with three green dreams of electric vehicle, energy storage station and solar farm, BYD looks forward to helping more countries and people to get rid of fossil energy over consumption crisis and environmental pollution, and strive to leave offspring a beautiful and clean world to live in.



In the daytime, solar panels capture solar energy like plants. At night, energy storage station transports the stored energy, like solar energy, wind energy, tidal energy, to thousands of families smoothly.

The electric vehicle, shuttling on the streets and lanes, is of zero emission, zero pollution.

Is this a dream?

This is the green dream of BYD and even all human beings.

Is this a dream?

No. We are already seeing it approaching us.





21.8%

Average cell efficiency up to 21.8%
Excellent optical performance

±5%

Power tolerance ±5%
Reliability for output performance

10
Years

10 years for product
25 years linear Warranty

Grid

Residential roof top systems
On/Off-grid commercial systems
On/Off-grid utility systems

3rd

Design loads: 3600 Pa for positive
(downward) and 1600 Pa for
negative (upward)

Safety factors Ym: 1.5



Certification

IEC61215-1(ed.1)
IEC61215-1-1(ed.1)
IEC61215-2(ed.1)
IEC61730-1(ed.2)
IEC61730-2(ed.2)

BYD

Monocrystal Silicone Modules

BYD MHK-30-5BB 300W-320W



BYD MHK-30-5BB 300W-320W


The country of manufacture is China

Mechanical Properties

| | |
|-----------------|--------------------------------------|
| Cell Type | 156.75mm*78.40mm |
| Number of Cells | 120 (12 ×10) pcs |
| Dimension | 1669mm*992mm*35mm |
| Weight | 18.9Kg |
| Front/Glass | 3.2mm tempered glass with AR Coating |
| Frame | Anodized aluminum alloy |
| Junction Box | IP67(3 Diodes) |
| Cable Type | 4.0mm ² *450mm |
| Connector | PV-ZH202B |

Temperature Coefficient

| | |
|--------------------------------|------------|
| TemP. Coeff. of Pmax (TK Pmax) | -0.328%/°C |
| TemP. Coeff. of Voc (TK Voc) | -0.254%/°C |
| TemP. Coeff. of Isc (TK Isc) | 0.041%/°C |



Packing Information

| | |
|------------------|--------|
| Packing Type | 40' HQ |
| Piece/Pallet | 30 |
| Pallet/Container | 26 |
| Piece/Container | 780 |

Electrical Properties

| Module Type | BYD300MHK-30 | BYD305MHK-30 | BYD310MHK-30 | BYD315MHK-30 | BYD320MHK-30 |
|---------------------------------|--------------|--------------|--------------|--------------|--------------|
| Open Circuit Voltage (Voc) (V) | 40.18 V±5% | 40.43 V±5% | 40.70 V±5% | 40.94 V±5% | 41.20 V±5% |
| Short Circuit Current (Isc) (A) | 9.58 A±5% | 9.67 A±5% | 9.77 A±5% | 9.87 A±5% | 9.98 A±5% |
| MPP Voltage (Vmp)(V) | 32.91 V | 33.10 V | 33.30 V | 33.50 V | 33.71 V |
| MPP Current (Imp) (A) | 9.12 A | 9.22 A | 9.31 A | 9.41 A | 9.51 A |
| Module Efficiency | 18.12% | 18.42% | 18.72% | 19.03% | 19.33% |
| Operating Temperature (°C) | -40°C~+85°C | | | | |
| Maximum System Voltage (V) | 1500 (VDC) | | | | |
| Maximum Series Fuse Rating (A) | 15A | | | | |
| Fire safety | Class C | | | | |
| Power tolerance | ±5% | | | | |

* Under Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

BYD COMPANY LIMITED.

ADD: Yan An Road, Kuichong, Longgang, 518119 Shenzhen, PEOPLE'S REPUBLIC OF CHINA