



Description

MG series single phase inverter is a new generation of PV string inverter which has been developed by INVT for residential users. MG series inverters have the advantages of compact size, light weight, easy installation and maintenance, and are above all cost efficient.

Features

- The core technologies are from Germany.
- Software optimization for the power grid with much wider adaptability.
- Global integrated monitoring and management, supporting all kinds of portable mobile devices.HMI is optional.
- Wider voltage range, lower starting voltage, higher conversion efficiency.
- Designed with latest thermal simulation technology for longer service life.

HMI Features

- Small and exquisite appearance.
- LCD display and easy to operate keyboard with multiple functions.
- Plug & play.



ACT witness Lab certified by TÜV SÜD



**G83/G59 C10/11
TF3.2.1 MEA PEA**



iMars PhoneExpert
(for IOS)



iMars PhoneExpert
(for Android)

Specification

	MG4KTL	MG4K6TL	MG5KTL	MG4KTL-2M	MG4K6TL-2M	MG5KTL-2M
Input (DC)						
Rated DC input power (W)	4000	4600	5000	4000	4600	5000
Max DC Voltage (V)	4500	5000	5500	4500	5000	5500
Starting Power (W)	50					
Starting Voltage / Min. Operation Voltage (V)	120/100					
MPPT Range (V)	120-550					
Number Of MPPT / String Per MPPT	1/2			2/1		
MAX.DC Current (A) Per MPPT x Number of MPPT	18x1	18x1	20x1	10x2	11x2	12x2
DC Switch	Optional					
Output (AC)						
Rated Power (W)	3680	4200	4600	3680	42000	4600
Max Power (W)	4000	4600	5000	4000	4600	5000
Max. AC Output Current (A)	19	21	23	16	21	23
AC Voltage Range	230/180-277Vac According to VDE-AR-N4105, G83/2, G59/3, AS4777/3100, CQC					
Grid Frequency	50Hz (44-55Hz) / 60Hz (54-65Hz) According to VDE-AR-N4105, G83/2, G59/3, AS4777/3100, CQC					
Power Factor	≥0.99 (Adjustable)					
THD	< 3% (At Rated Power)					
AC Connection	Single-phase (L, N, PE)					
System						
Cooling	Natural cooling					
Max. Efficiency	97.70%	97.70%	97.80%	97.90%	98.00%	98.00%
Euro-efficiency	96.50%	96.70%	96.80%	96.80%	96.80%	96.80%
MPPT Efficiency	99%					
Ingress Protection	IP65					
Consumption At Night	<1W					
Isolation Mode	Transformerless					
Operating Temperature	-25°C~+60°C, (derate after 45°C)					
Relative Humidity	0-95%, no condensation					
Protection	Over voltage protect; DC insulation monitoring; DC over current protection; monitoring; Grounding fault monitoring; island protection; Overheating protection; Electronic protection; Overvoltage and short circuit protection etc.					
Display And Communication						
Display	LED Display (standard) / LCD (Optional)					
System Language	English, Chinese, German, Dutch					
Communication Mode	RS485 (Standard), WiFi, Ethernet (Optional)					
Mechanical Parameters						
Diminsion (H x W x D mm)	405x360x150			460x360x150		
Weight (kg)	15			17		
Installation	Wall mounting					
Others						
DC Terminal	MC4					
Certifications	VDE-AR-N4105, G83/2, C10/11, TF3.2.1, AS4777/3100, CQCEN61000-6-1:4, EN61000-3-2:3, EN61000-11:12, IEC 62109-1:2010, LVRT					
Factory Warranty(Years)	5(standard) / 10, 15, 20 (optional)					



Sales E-mail: solar@invt.com.cn Service E-mail: solar-service@invt.com.cn Website: www.invt-solar.com

INVT Solar Technology (Shenzhen) Co., Ltd.

No. 7 Building, Gaofa Scientific Industrial Park, Longjing, Nanshan District, Shenzhen, China

Y6/1-06V(V2.2)